

It's no trick...
it's a vision system

VCSBC4018

The VCSBC4018 is an extremely fast intelligent single board camera and one of the fastest intelligent cameras all over with a computational power of 3200 MIPS rivalling a 2.6 GHz Pentium. It has 32 MB DRAM, 4 MB Flash EPROM for program and data storage and can acquire full frame 640 x 480 pixels at 32 frames per second!

The own internal operating system "VCRT" of the VCSBC4018 is multitasking. This means that user interface commands can execute in parallel without stopping the inspection process.

It has a video output onto a PC via 100MBit Ethernet interface and also a High Speed Trigger input with absolute constant capture delay, which allows absolutely jitter-free image acquisition even at very high speed processes.

And whereas a standard progressive scan camera gets a trigger, starts exposure and then reads out the pixel data, the VCSBC4018 has optimized the image acquisition process so that exposure and readout are in parallel.

The VCSBC4018 offers thus an extremely inexpensive entrance into the world of the high performance intelligent cameras.

All Vision Components cameras are built for industrial applications. They are insensitive to shock and vibration, and have multiple I/O lines for direct control of external equipment. For more complex control tasks, they can easily be interfaced to a PLC.



<u>Specifications</u>	VCSBC4018 <i>(Also available as colour version!)</i>
Sensor:	1/3", 640 (H) x 480 (V) Pixel
Shutter:	High-speed: up to 36,2 µsec in steps of 62,4 µsec Low-speed: up to 2 sec adjustable integration time
Integration:	Full Frame Progressive Scan
Frame rate:	32 fps
Acquisition:	asynchronous, program-controlled, or triggered externally, full-frame, Acquisition jitter free
A/D Conversion:	1 x 12.5 MHz / 10 Bit
Processor:	3200 MIPS, 400 MHz Texas Instruments TMS320C64xx
Video output:	Via 100Mbit Ethernet onto PC
Image-/data memory:	32 MBytes SDRAM
Flash memory:	4 MBytes Flash EPROM (non volatile memory) for programs and data, programmable in the system
Dig. I/O's:	2 inputs / 4 outputs optically decoupled 24V, Outputs 4 x 400mA, TTL I/O 4 In- and 4 outputs, 1 picture trigger input, 1 flash trigger output
Interface:	Ethernet 100 MBit TCP/IP
Supply voltage:	24V +/-20% DC, max. 300 mA
Electrical connections:	I/O (DC IN, PLC, 12-pin), Ethernet (8-pin), TTL I/O (20-pin), LED Lighting plug (4-pin)
Dimensions:	Approx. 60 x 80 x 35 mm

(No liability is assumed for possible errors!)